



全漢企業股份有限公司
FSP TECHNOLOGY INC.

台灣桃園市建國東路22號
No. 22, Jianguo East Road., Taoyuan City, Taiwan, R.O.C.
TEL:+886-3-375-9888
FAX:+886-3-375-6966

統一編號：84239055
Website : www.FSP-group.com
Email : sales@fsp-group.com.tw

SPECIFICATION



ESD08024023

FSP180-ADAN1

Released Date:2008/5/29-10:5:50



全漢企業股份有限公司
FSP TECHNOLOGY INC.

台灣桃園市建國東路22號 統一編號：84239066
No. 22, Jianguo East Road., Taoyuan City, Taiwan, R.O.C.
TEL: +886-3-375-9888 Website: www.FSP-group.com
FAX: +886-3-375-9966 Email: sales@fsp-group.com.tw

SPECIFICATION

AC Adapter

FSP180-ADAN1

Preliminary

P.E	R/D	APPROVED	REV.
Matisse	Stephen Li	LJ Wei	000

表單編號：7000P-0105



Electrical Specification

History

REV.	Description	Date	Drawn	Mechanical	Electrical	Approved
<u>000</u>	SPEC ISSUE	May.13'08	Gigi Yu	Matisse	Stephen Li	LJ Wei

MODEL NO. **FSP180-ADAN1**

SHEET 1 OF 6



Electrical Specification

Electrical Requirements

1. Input Characteristics:

ITEM	CONDITION	SPECIFICATION	
1.1 Rated Input Voltage		100Vac / 240Vac	
1.2 Input Voltage Range		90Vac to 264Vac	
1.3 Input Frequency Range		47Hz to 63Hz (± 1Hz)	
1.4 Input Current	100Vac, 240Vac / 10A Load	≤ 2.5A	
1.5 Input Current Harmonic		IEC61000-3-2	
1.6 Efficiency: (Warm up 10minutes later)	100Vac / 10A Load 240Vac / 10A Load	≥ 87% ≥ 89%	※ Meet 【CEC】 California Energy Commission
1.7 Power Saving	115Vac, 230Vac / 0A Load	≤ 0.5W	
1.8 Inrush Current	100Vac, 240Vac / 10A load	Shall be less than the rating of adapter critical component (including rectifiers, fuse surge and current limiting device)	

2. Output Characteristics:

※Measured at the end of DC cable.

MODEL NO. **FSP180-ADAN1**

SHEET 2 OF 6



Electrical Specification

ITEM	CONDITION	SPECIFICATION
2.1 Output Rated Voltage		18V
2.2 Output Current	at constant voltage mode	0A to 10A
2.3 Output Voltage Setting	at the output end of DC cable	18V \pm 5%
2.4 Output Voltage Ripple and Noise: (0.1uF Ceramic Cap. and 35V 47uF Aluminum Cap. Paralleled between the end of output cable)	100Vac / 10A Load 240Vac / 10A Load	\leq 380mVp-p
2.5 Turn-On Delay Time:	At 100Vac / 10A load, output voltage shall remain regulation	\leq 3Sec.
2.6 Hold Up Time:	At 100Vac or 240Vac / 10A load, output voltage shall remain regulation	\geq 5ms
2.7 Rise Time:	At 100Vac / 10A load, DC output rise time from 5% to 95% of Vo	\leq 50ms
2.8 Dynamic Load Change:	(1) Output load step is : 【1】 0 % ~50 % 【2】 50 %~100 % (2) S/R=0.5A/us (3) Frequency is 100Hz and 1KHz	18V \pm 10%
2.9 Overshoot	100Vac, 240Vac / 0A and 10A Load	18V \pm 10%

MODEL NO. **FSP180-ADAN1**

SHEET 3 OF 6



Electrical Specification

3. Protection Characteristics:

ITEM	CONDITION	SPECIFICATION
3.1 Short Circuit Protection:	When an internal fault occurs, or an external fault is applied to the power supply, such that an overload or short circuit is applied to the output, the power supply shall shut down and enter auto-recovery mode.	Shutdown and no damage
3.2 Over-Voltage Protection	The output voltage will enter into shut down that means no output while over voltage happened at output terminal that caused by internal fault. The output trip voltage will be less than 130% of its voltage rating.	Shutdown and no damage
3.3 Over Power Protection:	When an internal fault occurs, or an external fault is applied to the power supply, such that an overload or short circuit is applied to the output, the power supply shall shut down and enter auto-recovery mode.	Shutdown and no damage
3.4 Over Temperature Protection:	The power supply will enter into shut down while the abnormal thermal rise occurs. It will enter into normal condition if the fault condition is removed.	No fire, no smoke

MODEL NO. **FSP180-ADAN1**

SHEET 4 OF 6



Electrical Specification

4. Environmental Characteristics:

ITEM	CONDITION	SPECIFICATION
4.1 Electric Fast Transients : Refer to IEC61000- 4-4	Impulse: $\pm 1\text{kV}$ applied to L,N	Normal operation shall be continued.
4.2 Lightning Surge: Refer to IEC61000-4-5	$\pm 1\text{kV}$ applied differential mode	Normal operation shall be continued.
	$\pm 2\text{kV}$ applied common mode	Normal operation shall be continued.
4.3 Electron Static Discharge: (Refer to IEC61000-4-2 Energy Storage Capacitor 150pF; Discharge Resistor 330 Ω)	Air Discharge: $\pm 15\text{KV}$ Contact Discharge: $\pm 8\text{KV}$	Normal operation shall be continued.
4.4 Cooling	Natural air cooling	
4.5 EMI: Adapter comply with the following national standards: EMI Conducted Emission EMI Radiated Emission	1.Full Load 2. The power supply with internal filter can meet.	FCC PART 15J CLASS B CISPR22 EN55022 CLASS B VCCI LEVEL II
4.6 Safety conforming:		Regulated by customer
4.6.1 California Energy Commission 【CEC】		Comply with CEC standard
4.7 Leakage Current	254Vac / 50Hz	$\leq 0.25\text{mA}$
4.8 Dielectric Strength: (Hi-Pot)	Between AC input and secondary applied AC 1.5KV / test time 1 minute / cut off current shall be less than 10mA	
4.9 Temperature:	Operating Storage	0 to 40°C -20 to +80°C
4.10 Humidity:	Operating Storage	20% ~ 80% 10% ~ 90%

MODEL NO. **FSP180-ADAN1**

SHEET 5 OF 6



Electrical Specification

5. Mechanical Characteristics:

ITEM	CONDITION	SPECIFICATION
5.1 Dimension (Length x Width x Height)		170 X 85 X 41mm
5.2 Adapter weight		860g (typical)
5.3 Input AC socket Type		IEC 320-C14 Type
5.4 Output DC Cable Length Wire style		L=1800±50mm UL 1571 14AWG
5.5 Vibration Test	(1) Non-operating, 0.01g ² /Hz at 5Hz slopping to 0.02g ² /Hz at 20Hz, And maintain 0.02g ² /Hz from 20Hz ~ 500Hz (2) PSD=3.13grms, 15 minutes/axis (3) Vibration duration:15minutes (4) Vibration waveform:Random (5) Force Direction X,Y,Z	Normal operation shall be continued.

MODEL NO. **FSP180-ADAN1**

SHEET 6 OF 6